enquiry@estmech.com

DESALINATION & WATER TREATMENTS



FILTRATION PROCESSES

- > Filtration
 - Strainers
 - FTAUR
 - Miscellaneous
 - Nozzles
- > Microfiltration
 - Cartridge filters
 - Cartridges
- > Ultrafiltration
- > Nano filtration

JIDP Jurong Island Desalination Plant









FRP/GRP Cartridge Filter Housings Capacity: 137.000 m3/d (~30 million gallons per day)

Client: ST Engineering Marine

Ultimate owner: PUB Singapore's National Water Agency





Filters

Cartridge filters

FTP (GRP)

FTI (SS, CS)

FTPV (PVC)

Automatic backwash filters

FTAUR (GRP/SS, CS)

Basket filters/strainers

FTC (GRP/SS, CS)













NSF International

789 N. Dixboro Road, Ann Arbor, MI 48105 USA

RECOGNIZES

Fluytec S.A.

Spain

AS COMPLYING WITH NSF/ANSI/CAN 61 AND ALL APPLICABLE REQUIREMENTS.

PRODUCTS APPEARING IN THE NSF OFFICIAL LISTING ARE

AUTHORIZED TO BEAR THE NSF MARK.





Certification Program Accredited by the American National Standards Institute



Certification Program Accredited by the Standards Council

This certificate is the property of NSF International and must be returned upon request. This certificate remains valid as long as this client has products in Listing for the referenced standards. For the most current and complete Listing information, please access NSF's website (www.nsf.org).

David Purkiss

Vice President, Global Water Division